YORU Cable Ties Datasheet



Model YR200-12HMB
Size Label 8" x 12.0 mm.



Type Hook & Loop Material Nylon Fabric Flammability ROHS Compliant Yes UL Recognized Releasable Closure Yes 8 inch (Imperial) 200 mm. (Metric) 12.00 mm. (Body) 21.00 mm. (Body) 21.00 mm. (Body) ± 10% -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) Minimum Tensile Strength 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)		
None	Color	Black
ROHS Compliant Yes	Туре	Hook & Loop
ROHS Compliant Yes	Material	Nylon Fabric
UL Recognized No Releasable Closure Yes 8 inch (Imperial) 200 mm. (Metric) 12.00 mm. (Body) 21.00 mm. (Head) Thickness ≈ 0.80 mm. (Body) ± 10% -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Flammability	None
Releasable Closure Yes Length 8 inch (Imperial) 200 mm. (Metric) Width 12.00 mm. (Body) 21.00 mm. (Head) Thickness ≈ 0.80 mm. (Body) ± 10% Operating Temperature -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) Minimum Tensile Strength 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	ROHS Compliant	Yes
Length 8 inch (Imperial) 200 mm. (Metric) Width 12.00 mm. (Body) 21.00 mm. (Head) Thickness ≈ 0.80 mm. (Body) ± 10% -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) weight ≈ 0.90 grams (1 piece)	UL Recognized	No
Length 200 mm. (Metric) Width 12.00 mm. (Body) 21.00 mm. (Head) Operating Temperature ~ 0.80 mm. (Body) ± 10% -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) Minimum Tensile Strength 0.0 lbs (Imperial) Bundle Diameter 5.0 mm. (Minimum) 5.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Releasable Closure	Yes
200 mm. (Metric)	Length	8 inch (Imperial)
Width 21.00 mm. (Head) Thickness ≈ 0.80 mm. (Body) ± 10% Operating Temperature Image: I		200 mm. (Metric)
21.00 mm. (Head) Thickness ≈ 0.80 mm. (Body) ± 10% Operating Temperature -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) O.0 lbs (Imperial) 0.0 Kgs (Metric) Bundle Diameter 5.0 mm. (Minimum) 50.0 mm. (Maximum) weight ≈ 0.90 grams (1 piece)	Width	12.00 mm. (Body)
Operating Temperature -1.4°F to +219.2°F (Fahrenheit) -17°C to +104°C (Celsius) 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight * 0.90 grams (1 piece)		21.00 mm. (Head)
Operating Temperature -17°C to +104°C (Celsius) 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Thickness	≈ 0.80 mm. (Body) ± 10%
-17°C to +104°C (Celsius) 0.0 lbs (Imperial) 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Operating Temperature	-1.4°F to +219.2°F (Fahrenheit)
Minimum Tensile Strength 0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)		-17°C to +104°C (Celsius)
0.0 Kgs (Metric) 5.0 mm. (Minimum) 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Minimum Tensile Strength	0.0 lbs (Imperial)
Bundle Diameter 50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)		0.0 Kgs (Metric)
50.0 mm. (Maximum) Weight ≈ 0.90 grams (1 piece)	Bundle Diameter	5.0 mm. (Minimum)
		50.0 mm. (Maximum)
	Weight	≈ 0.90 grams (1 piece)
Features Easy operation, Good insulation, Self-locking, Reusable.	Features	Easy operation, Good insulation, Self-locking, Reusable.







Pictures of products and dimensions are approximate and subject to technical changes (with a tolerance of \pm 5%).